

Interior Finishes

- 1 1/4" quartz countertops in kitchen and bathrooms
- 42" upper cabinets with choice of colour and style from our suppliers (Maple, Melamine or Thermafoil)
- Full depth cabinet over fridge
- Soft close cabinets in kitchen
- Pot and pan drawers \$5000 credit for appliances
- Single border row ceramic tile around tubs and shower
- Mirrors full width of vanity
- Semi-frameless single shower door

- Choice of standard package
- bathroom hardware

File floors in wet areas • Laminate flooring on main level Carpet on upper level and stairs •

• Square vertical drywall corners California

• Paint or stain on railings with Iron spindles

8lb carpet underlay

Knockdown ceilings

Painted basement stairs

- 3 hinges on all interior doors
- Swing doors on closets

- **Electric, Heating &** Plumbing
- 4 LED lights on main floor
- 3 pendant lights in kitchen .
- 1 electric fireplace • 150 amp electrical service with 60 breaker capacity
- 220V service to dryer and range
 Decor light switches and outlets
- 2 Island outlet as per plan
- · Soffit outlet with switch
- GFI protection in all bathrooms
- 3 GFI exterior weatherproof outlets
- Arc fault protection outlets for bedrooms Structured wiring run into mechanical room
- Rough in central vacuum
- Wired smoke and CO detectors Programmable thermostat
- Forced air heating with drip humidifier Gas line to main kitchen
- Bath fan
- Furnace and ducts power vacuumed prior to possession
- Waterline to fridge
- Floor drain at laundry location
 Shut off valves to all toilets and sinks
- 1 soaker tub in master bath

Exterior, **Doors &**

Windows

Fibreglass exterior doors

basement windows

keyless entry

Half glass/rear garden door
57 x 33" slider

Fiber insulated garage door

Belt driven garage door

opener with 2 remotes and

Garage heater rough in

Framing

 Engineered floor and truss system Roof trusses 24" on

- centre 18" overhang
- Tongue and grooved OSB subfloor, glued & screwed
- 3/8" OSB on roof with H clips
- 3/8" spruce underlay in
- tile areas 24"
- Wood framed basement walls on center
- 2 x 6 spruce stud exterior
- walls, 3/8" OSB walls
- 25 year warranty on
- asphalt shingles

Energy Efficient **Features**

- High efficiency single stage furnace
- Low flush toilets
- Low flow taps and
- shower heads
- Insulated rim joists
- around perimeter
- R-40 fibreglass insulation in attic
- R-20 insulation on all floors Insulated exterior door
- Windows are PVC integral frame with jamb
- **Triple Pane Window**

Standard Spec Features | 2024

This design is published by Active Homes I to all rights reserved including the reproduction in whole

587-524-1131 | sales@activehomes.ca

ActiveHomes.ca

- washed rock
- exterior foundation
- Weeping tile around perimeter with 6" of washed rock • Garage floor has 10mm rebar with reinforced 24" on
- Poured sidewalk to front step piles or brackets with

9' foundation wall height 9' main floor ceiling height 18 x 8" 25 MPA concrete footing Basement walls 8" thick, 10mm rebar, 20 MPA concrete

- Floors are 3 1/2" thick poured over 6 mil poly and
- Asphalt emulsion spray to damp roof of the
- center and piles Concrete driveways
- 10mm reinforcement

