



Front Attached 24' | Single Family Home



- 2 Story Custom Fireplace
- Main Floor Full Bath
- Bonus Room
- 9' Ceilings
- Spice Kitchen
- Double Attached Garage
- 5 Piece Ensuite Side Entrance
- Main Floor Bedroom / Den
- Open to above Great Room
- Upper Floor Laundry
- Quart Countertops





587-524-1131 | sales@activehomes.ca



Interior Finishes

- 1 1/4" quartz countertops in kitchen and bathrooms
- 42" upper cabinets with choice of colour and style from our suppliers (Maple, Melamine or Thermafoil)
- Full depth cabinet over fridge
- Soft close cabinets in kitchen
- Pot and pan drawers \$5000 credit for appliances
- Single border row ceramic tile around tubs and shower
- Mirrors full width of vanity
- Semi-frameless single shower door

- Choice of standard package
- bathroom hardware
- Tile floors in wet areas Laminate flooring on main level Carpet on
- upper level and stairs •
- 8lb carpet underlav
- 3 hinges on all interior doors
- Swing doors on closets
- Square vertical drywall corners California
- Knockdown ceilings • Paint or stain on railings with Iron spindles
- Painted basement stairs



Electric, Heating & Plumbing

- 4 LED lights on main floor 3 pendant lights in kitchen
- 1 electric fireplace
- . 150 amp electrical service with 60 breaker capacity
- 220V service to dryer and range Decor light switches and
- outlets
- 2 Island outlet as per plan
- Soffit outlet with switch
- GFI protection in all bathrooms 3 GFI exterior weatherproof outlets
- Arc fault protection outlets for bedrooms Structured wiring run into mechanical room
- Rough in central vacuum
- Wired smoke and CO detectors Programmable thermostat
- Forced air heating with drip humidifier Gas line to main kitchen
- Bath fan
- Furnace and ducts power vacuumed prior to possession
- Waterline to fridge
- Floor drain at laundry location Shut off valves to all
- toilets and sinks
- 1 soaker tub in master bath
- Garage heater rough in

Framing

system Roof trusses 24" on

- centre 18" overhand Tongue and grooved OSB
- subfloor, glued & screwed • 3/8" OSB on roof with H clips
- 3/8" spruce underlay in
- tile areas 24"
- Wood framed basement walls on center
- 2 x 6 spruce stud exterior
- walls, 3/8" OSB walls
- 25 year warranty on
- asphalt shingles

Energy Efficient **Features**

- High efficiency single stage furnace
- Low flush toilets
- Low flow taps and
- shower heads
- Insulated rim joists
- around perimeter
- Insulated exterior door
- frame with jamb

Standard Spec Features | 2024

This design is published by Active Homes Ltd., all rights reserved, including the reproduction in whole or in

587-524-1131 | sales@activehomes.ca



d details shown are approximate and may be subject to change witho

center and piles Concrete driveways 10mm reinforcement

Structural & Concrete

- 9' foundation wall height 9' main floor ceiling height • 18 x 8" 25 MPA concrete footing Basement walls
- 8" thick, 10mm rebar, 20 MPA concrete
- Floors are 3 1/2" thick poured over 6 mil poly and washed rock
- Asphalt emulsion spray to damp roof of the exterior foundation
- Weeping tile around perimeter with 6" of washed rock • Garage floor has 10mm rebar with reinforced 24" on
- Poured sidewalk to front step piles or brackets with

- R-40 fibreglass insulation in attic • R-20 insulation on all floors
 - - Windows are PVC integral
 - **Triple Pane Window**

- Engineered floor and truss
- Half glass/rear garden door
 57 x 33" slider
- basement windows

Exterior,

Doors &

Fibrealass exterior doors

Windows

- Fiber insulated garage door Belt driven garage door opener with 2 remotes and
- keyless entry